

CITIZEN

Fast, tough and easy to use receipt printer

Protected by Spill-Shield™



One touch top cover

Spill-Shield™ design to prevent damage from moisture or foreign objects to the internal mechanism. This makes it the best protected printer at the POS. No matter where you are: bar, restaurant or shop nothing can stop your printer to do it's job.

Internal power supply

All 80mm POS printers from Citizen offer an internal power supply.

CT-S2000

Other

Applications

- Hospitality
- Journal
- Kiosk
- Kitchen
- Retail



Confidence in point-of-sale

TOMORROW'S PRINTING TODAY

Citizen Systems Europe GmbH, Waterfront, Lotus Park, Staines-Upon-Thames, TW18 3AG, United Kingdom, +44 20 8893 1900

CITIZEN SYSTEMS EUROPE GMBH



USB is default in addition to serial or parallel interface boards. This makes the CT-S2000 a future-proof investment.

Specifications

Model	CT-S2000
Printing Technology	Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	220 mm /sec.
Print Width (maximum)	80 mm
Media Width (min to max)	58 / 60 / 80 / 82.5 mm
Roll Size (max), Core Size	102 mm outside diameter
Main Interface	Dual Interface Serial (RS-232C), USB (version 2.0, full speed)
Optional interfaces	Ethernet (SEH), Serial (RS-232C compliant), Parallel (IEEE 1284 compliant)
Power supply	100 - 240V, 50/60hz
Reliability	200 Million pulses or 150 Km, 2 million cuts
Emulations (Languages)	ESC/POS™
Drivers and software	Free-of-charge from website, including support for various platforms
Flash (Non-Volatile Memory)	384K bytes
Size (W x D x H) and Weight	147x207x147 mm, 1.2 Kg (AC type) / 1.8 Kgs (DC type)
Cutter	Guillotine type, full and partial
EMC and safety standards	CE, TUV, UL, C-UL, FCC class A

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

CT-S2000

Other

Features & Benefits

- Paper exit: Front exit, top loading
- Printing Speed: Fast print out of receipts - up to 220mm per seconds
- Low space requirement - integrated power supply enables clean work station
- Easy notification - built-in buzzer



The fully loaded high end thermal printer with built in protection