



ZBAMB2011T
Deactivator Antenna,
Countertop

The Sensormatic Value Pad Deactivator deactivates active AM EAS labels up to four inches above the surface of the pad for a reliable and virtually seamless process while expediting throughput at the point-of-sale (POS). This unit uses a two-step detect and deactivate process. The integrated status indicators provide visual and audible notifications when live labels are successfully detected and deactivated.

In addition, the deactivator acts as a double-checking device if an associate is ever uncertain whether the label was deactivated. The integrated keypad allows associates to control the volume and tone of the deactivator to distinguish it from other POS equipment. The keypad also initiates the "power-save" mode to help prevent theft by turning the unit off.

With a variety of installation options available – countertop, vertical and flush mount – the sleek design and small footprint maximizes POS counter space. The Value Pad operates off an ordinary electrical outlet and does not require a separate controller. The deactivator can be integrated with the Sensormatic Shrink Management as a Service analytics platform which provides device management along with predictive insights to help retailers reduce shrink, optimize labor, and increase sales.

Retailer Values

- Scan-enable functionality only deactivates labels with a valid barcode
- Slim design allows maximum use of POS space
- EAS connectivity option allows for generation of operational information to help quickly identify and correct performance
- Built-in audible and visual indicators provide immediate feedback when active labels are detected and deactivated

Product Codes

ZBAMB2011T

Deactivator Antenna, Countertop Mounting Bracket, Power Cord

ZBAMB2011F

Deactivator Antenna, Flushmount Bracket, Power Cord

ZBAMB2011U

Deactivator Antenna, Under the Counter Mounting Bracket, Power Cord

ZBAMB2011

Deactivator Antenna Only

ZBFM-B1

Flushmount Mounting Bracket

ZPCM-B5

Tabletop Vertical Mounting Bracket

ZPCM-B6

Tabletop Sidewall Mounting Bracket

Product Compatibility

- All Sensormatic AM EAS Labels
- Wireless Device Manager
- Wireless Module
- Shrink Management as a Service
- Deactivation Remote Alarm Module

Specifications

Length	21 cm (8.3in)
Width	16cm (6.3in)
Height.....	4cm (1.6in)
Weight	0.95kg (2.1lb)
Power Cord Length.....	170cm (5.5ft)
Power Supply Weight	0.28kg (0.6lb)

Electrical

Deactivator

Input Voltage..... 18Vdc, 1.7A

Separate Power Supply

Input Voltage..... 100–240Vac, 50/60Hz

AC Line Current..... 1Arms (max.)

Output Voltage..... 18Vdc, 1.7A Listed
Class 2

Certified Limited Power Source

CE This product is in conformity with Directive 2011/65/EU (RoHS 2) and 2015/863 (RoHS 3) on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS).

Environmental Constraints

Operating Temperature

0°C to 35°C (32°F to 95°F)

Enclosure

0 to 90%, non-condensing

Declarations

EMC

47 CFR Part 15

RSS 210

EN 300330

EN 301489

Safety (second edition)

UL62368-1

CSA C22.2.60950-1

EN 62368-1

EMF

EN 50364

CE This product is in conformity with Directive 2011/65/EU (RoHS 2) and 2015/863 (RoHS 3) on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS).