

CITIZEN

Internal Peel & Rewind

High-speed industrial printing



Space-saving design concept

The Hi-Open™ case lifts up vertically meaning that the printer's footprint does not change as the cover is opened making it ideal for tight spaces.

Front loading rewinder

The clever and unique CL-S700RII includes an internal rewinder that is simplicity itself to use. The front door drops down and the liner or labels are loaded.

Easy configuration

The large graphic LCD gives a clear indication of printer status and easy printer configuration.

CL-S700RII

Label, Industrial

Applications

- Courier
- Logistic / Transport
- Manufacturing
- Retail
- Warehousing



High performance with easy access

TOMORROW'S PRINTING TODAY

Citizen Systems Europe GmbH, Waterfront, Lotus Park, Staines-Upon-Thames, TW18 3AG, United Kingdom, +44 20 8893 1900

CITIZEN SYSTEMS EUROPE GMBH

Specifications

Model	CL-S700RII
Printing Technology	Thermal Transfer + Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	10 inches per second (254 mm/s)
Print Width (maximum)	4 inches (104 mm)
Media Width (min to max)	1 - 4.6 inches (25.4 - 118 mm)
Roll Size (max), Core Size	Outside diameter 8 inches (200 mm) Core size 1 inch (25mm) Plus Outside media slot
Media Thickness (min to max)	63.5 to 254 µm
Media Length (min to max)	0.25 to 99.99 inches (6.35 to 2539.74mm)
Media Sensor	Fully adjustable rear sensor and high resolution front sensor
Main Interface	Triple interface USB, parallel and serial built-in, exchangeable interface card slot for optional card
Optional interfaces	Wireless LAN 802.11b and 802.11g standards, 100 metres, 64/128 bit WEP, WPA, up to 54Mbps, Ethernet (10/100 BaseT)
Ribbon size	3.4 inches (86.5 mm) maximum outside diameter. 450 metres length.
Ribbon winding & type	Ink side in or out, automatically sensing. Wax, Wax/Resin or Resin Type
Ribbon system	ARCP™ automatic ribbon tension adjustment
Mechanism	Hi-Lift™ metal mechanism with wide opening head
Control panel	4 buttons, 4-line back-lit graphic LCD
Emulations (Languages)	Cross-Emulation™ - autoswitch between Zebra® and Datamax® emulations, Datamax® DMX, Zebra® ZPL2® , CBI™ BASIC Interpreter, Eltron® EPL2®
Drivers and software	Free-of-charge on CD with printer, including support for various platforms
Flash (Non-Volatile Memory)	16 MB total, 4MB available for user
Size (W x D x H) and Weight	255 x 490 x 385 mm, 17.6 Kg

CL-S700RII

Label, Industrial

Features & Benefits

- Paper load: Front access for all operations including media and ribbon changing
- Printing Speed: Ultra fast print out - up to 250mm per second (10 inches per second)
- Media support: Very large media capacity - holds rolls up to 8 inches (200 mm)
- Ribbon options: Wide range of ribbon options - Uses up to 450 metres inside and outside wound ribbons
- Display: Backlight LCD control panel for easy configuration
- Hi-Open™ case for vertical opening, no increase in footprint and safe closing.
- No more unreadable labels - the ARCP™ ribbon control technology assures clear prints.
- ENERGY STAR® compliant
- Recyclable packacking

Model	CL-S700RII
-------	------------

Warranty 2 years on printer. 6 months or 50 Kms printhead

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0